

Halogen Wet Tap Remover Kit

Overview

The Wet Tap Remover Kit is used to install Halogen's MP5 Sensors into an active distribution line. Conventional Wet Tapping equipment is used to tap the pipe and install a Corp Stop Valve. This enables both the installation and servicing of sensors located in the municipality distribution lines.



Options

Remover Tool: Speeds removal by simultaneously driving both remover nuts with a drill or impact driver

Mounting: Use with 2" Corp Stop Valve such as Muehler

Features and benefits

- Enables servicing without shutdown
- For pipelines 4" for greater
- Great for dead end monitoring

Not Included

- Wet Tap Valve PN
- Wet Tap Kit for 2" MIP valve







Remover Kit

Technical Specifications*

Overall	
Pressure limit	10 bar (145 psi)
Wet Tap Drill Equipment	2" Wet Tap Drill
Valve	2" MIP or AWWA X MIP Threads
Weight	4 lbs.
Threads	British, Metric or 2" NPT
Environmental	
Operating temperature	-20 to 60°C (-4 to 140°F) (8W (AC)/9W (DC) sensor load)

* Subject to change without notice

Order Information

D-H1WT-P	Wet Tap Sensor (for use with RMR-WT)		
RMR-WT	Wet Tap Remover for 2" Corp Stop Valve		
CORP	2" Corp Stop Valve		
CABL-1001	Cable Adder (5' Standard) 10, 20, or Custom Length		
RMVRTL	Remover tool	